# **NEW** Ishida Astra II

Price Computing Scale with Printer



- 84 one-touch preset keys, 168 presets (assign two items/key 0)
- · Programmable function keys
- Blue alphanumeric LCD display (23 digits, 16 segments)
- Print speed of 3.9 in (100 mm) per second
- · Convenient side-loading label feature
- TC/IP 10/100 Base T Ethernet
- USB port (for data backup and restore)
- · Proportional tare
- · Optional customer display
- NTEP Certified, Legal for Trade

# Part Number/Price

Part #	Model	Capacity	Weight	Price
185822	Astra II Bench	30 lb x 0.01 lb	25 lb	Consult
185823	Astra II Pole	30 lb x 0.01 lb	25 lb	Consult
190641	Astra II Lite software CD			\$0.00
190642	Astra II Lite license file (for one computer only not transferable)			Consult

# **Options/Accessories**

Part #	Description	Price
47977	Produce platter (sits on top platter included with scale)	Consult
47976	Fish platter (sits on top platter included with scale)	Consult
47341	Continuous roll thermal journal paper, 64 mm W x 50 m L (for reports only)	Consult
184273*	Technical manual	Consult
184270*	Additional operating manual	Consult
184274*	Additional operation card	Consult
47732	2.36 in x 1.73 in (60 mm x 44 mm)	Consult
47733	2.52 in x 1.85 in (64 mm x 47 mm)	Consult
47735	2.52 in x 2.32 in (64 mm x 59 mm)	Consult
47736	Pre-printed safe handling instructions, 2.52 in x 2.32 in (64 mm x 59 mm)	Consult
47743 ***	Extended text, 2.52 in x 3.34 in (64 mm x 85 mm)	Consult
47745	Pre-printed safe handling instructions on top of label, 2.52 in x 3.34 in (64 mm x 85 mm)	Consult
47762	Non-barcode, 2.52 in x 1.46 in (64 mm x 37 mm)	Consult

Label Stock, please consult factory for case quantity pricing. Examples shown on page 956 Labels sold by the case-12 rolls per case.

# **Specifications**

Capacity: 30 lb x 0.01 lb

**Weighing Resolution:** 3,000 display divisions maximum

**Display Types:** LCD, blue alphanumeric (23 digits, 16 seg)

**Display Items:** Tare: Four-digits Unit price: Five-digits
Total price: Six-digits

### Preset Keys:

84 one-touch preset keys 168 presets (assign two items/key)

# **Memory Capacity:**

2 MB

**Communications:** TCP/IP 10/100 Base T Ethernet

### Platter:

14.5 x 10.5 in (368 x 268 mm)

**Printing Speed:** 3.9 in (100 mm) per second

Printing: Direct thermal 2.2 in (56 mm) (448 dot, 8 dot/mm)

**Label Size:**Width: 1.5-2.5 in (38-64 mm) {min}
Length: 1.2-6.9 in (30-175 mm) {max}

### Label Roll:

Inside diameter: 1.6 in (40 mm) Outside diameter: 3.9 in (100 mm)

# **Label Backing Paper:**

Width: Up to 2.6 in (66 mm)

# Power Supply: AC100-240V, 50/60 Hz

Power Consumption: Stand-by: 50 W In operation: 100 W

### **Classification:**

NTEP CC 07-005 UL Listed

Warranty: One-year limited warranty

<sup>\*</sup> Manuals and software programs can be downloaded at no charge from our website at www.ricelake.com

<sup>\*\*\*</sup> Safe handling instructions can also be printed by scale



Price Computing Scale with Printer

# **Dimensions: Bench**

Unit

17.2 in x 16.1 in x 6.3 in (437 mm x 410 mm x 159 mm)

### **Stainless Steel Platter**

10.5 in x 14.6 in (268 x 370 mm)

### **Dimensions: Pole**

### Unit

17.2 in x 16.1 in x 6.3 in (437 mm x 410 mm x 159 mm)

### **Stainless Steel Platter**

10.5 in x 14.6 in (268 x 370 mm)

### **Unit with Pole**

19.7 in x 16.1 in x 20.6 in (500 mm x 410 mm x 524 mm)







