

Rice Lake RS-130/RS-160

Battery-Operated Price Computing Scales



RS-130 Pole



RS-160 Bench

Part Number/Price

Part #	Model	Capacity	Weight	Price
167941	RS-130 Bench	30 lb x 0.01 lb 15 kg x 0.005 kg 480 oz x 0.2 oz	12 lb	Consult
168100	RS-130 Pole	30 lb x 0.01 lb 15 kg x 0.005 kg 480 oz x 0.2 oz	13 lb	Consult
167942	RS-160 Bench	60 lb x 0.02 lb 30 kg x 0.01 kg 960 oz x 0.5 oz	12 lb	Consult
168101	RS-160 Pole	60 lb x 0.02 lb 30 kg x 0.01 kg 960 oz x 0.5 oz	13 lb	Consult

NOTE: Buy quantity of 5 and get a 50% discount

Options/Accessories

Part #	Description	Price
169634	Additional operating manual	Consult
169635	Additional calibration instructions	Consult
85711	Additional in-use cover	Consult
47976	Fish platter, (W x D) 9.5 x 13.5 in	Consult
47977	Produce platter, (W x D) 9.5 x 13.5 in	Consult
85710	Replacement rechargeable battery, 6V	Consult

Dimensions: Bench

Unit

11.8 in x 13.0 in x 4.7 in
(300 mm x 330 mm x 120 mm)

Stainless Steel Platter

11.8 in x 9.5 in (300 mm x 240 mm)

Dimensions: Pole

Unit

11.8 in x 13.0 in x 4.7 in
(300 mm x 330 mm x 120 mm)

Stainless Steel Platter


11.8 in x 9.5 in (300 mm x 240 mm)

Head

11 in x 3.1 in (280 mm x 78 mm)

Unit with Pole

11.8 in x 9.5 in x 16.1 in
(300 mm x 240 mm x 410 mm)



Standard Features

- Toggle between lb/kg/oz*
- Nine PLU keys for direct price lookups
- Function keys: change, unit, zero, tare
- Backlit LCD display, 0.45 in (11.5 mm) character height
- Cash back calculation
- Large stainless steel platter
- In-use cover
- Pole swivels to face desired direction
- Battery charge indicator
- Internal sealed battery included
- Optional customer display
- NTEP Certified, Legal for Trade

*Not Measurement Canada Approved

Specifications

Capacity/Graduations:

RS-130:

30 lb x 0.01 lb
15 kg x 0.005 kg
480 oz x 0.2 oz

RS-160:

60 lb x 0.02 lb
30 kg x 0.01 kg
960 oz x 0.5 oz

Display Items:

Weight: Five-digits
Unit price: Five-digits
Total price: Six-digits

Accuracy:

1/3,000

Display:

Backlit LCD, 0.453 in (11.5 mm) character height

Power Source:

DC 6V/25 mA rechargeable battery with AC adaptor included AC 115V/0.1A (max) (100+ hours battery life, 8-10 hours to recharge)

Weight:

10 lb (4.5 kg)

Preset Key:

Nine direct price lookups

Dimensions:

Platter: (W x D) 11.8 x 9.5 in
Overall: (W x D x H) 12.3 x 13.0 x 4.7 in

Operating Temperature:

14°F to 104°F (-10°C to 40°C)

Classification:

NTEP CC 04-067, Class III 3000d

*Not Measurement Canada Approved

Warranty:

One-year limited warranty

